



# MASTER SOLID TIRE CATALOG

Flat proof solid tires, so no more downtime period.



# OUR HISTORY

---

## SENTRY TIRE & RUBBER, LLC.

Started producing V-Belts, Conveyor Belts and other rubber accessories back in the 70's. As our manufacturing knowledge and technique matured, we began producing pneumatic OTR tires and solid tires.

Today we are a global company with modern manufacturing facilities in Vietnam, China and Taiwan. With these capabilities, we are able to export a combined total of \$100 million USD annually in all product segments. Our products are sold in over 25 countries worldwide and in all industries such as mining, recycling and other industrial applications.

Supported by our technical and manufacturing expertise, Sentry Tire & Rubber LLC. was created in 2005 to help distribute our product in the U.S. With emphasis on quality and service, we strive to bring the two most important attributes U.S. consumers and distributors come to expect. Our team of knowledgeable professionals are dedicated to bringing the best industrial tire product to you. In addition, our engineers continue to find new ways provide product innovations to help our customers work more efficiently with less down time.

We believe that providing an easy to use product to our customer and making it easy for our distributors to sell our product to those customers is our path to success. This is a challenge that we are committed to meet.





# TABLE OF CONTENTS

---

## FORKLIFT TIRE SERIES



**6** K Pattern



**7** M Pattern



**8** Press-On Banded Traction



**8** Press-On Banded Smooth



**9** S Pattern



**10** SD Pattern



**11** Y Pattern

## LOADER TIRE SERIES



**13** OD Pattern



**14** S Pattern



**15** S1D Pattern



**16** S2D Pattern



**17** VD Pattern



**18** ZD Pattern

## SKID STEER TIRE SERIES



**20** SD Pattern



**21** VD Pattern



**22** OD Pattern

## TELEHANDLER TIRE SERIES



**24** VD Pattern



**25** SD Pattern





# SOLID PNEUMATIC FORKLIFT TIRE SERIES





## SOLID K PATTERN TIRES | Traction with Maximum Durability

SENTRY TIRE SOLID PNEUMATIC DURAECO FORKLIFT SERIES



### Design Features

- Aggressive tread design for maximum traction in harsh conditions.

### Deep Tread Design

- Aggressive tread design allows for maximum traction in challenging environments.

### K Pattern Features:

- Designed for all applications where superior traction is required.
- Deep side treads provide for extra traction while operating in outdoor applications.
- Smooth center reduces traction that causes extra spin resulting in faster wear.
- Ideally used in situations where machine operates in harsher applications.
- Also available in Non-Marking.

| TIRE SIZE  | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|------------|---------------|-----------------|-----------------------|---------------------|--------------|
| 8.15-15    | 6.50          | 8.30            | 32.80                 | 9259.40             | 205.00       |
| 8.25-15    | 7.00          | 8.30            | 28.00                 | 6613.80             | 138.90       |
| 7.00-12    | 5.00          | 6.70            | 26.00                 | 5291.00             | 105.80       |
| 6.50-10    | 5.00          | 6.50            | 23.00                 | 3968.30             | 83.80        |
| 6.00-9     | 4.00          | 6.20            | 20.50                 | 3196.70             | 60.60        |
| 5.00-8     | 3.00          | 5.10            | 18.00                 | 2425.10             | 38.60        |
| 300-15     | 8.00          | 10.40           | 32.80                 | 11023.10            | 257.90       |
| 27 x 10-12 | 8.00          | 9.40            | 27.00                 | 7716.20             | 167.50       |

\*For more information and a full list of available sizes, please visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID M PATTERN TIRES | Enhanced Traction for Indoor and Outdoor

SENTRY TIRE SOLID PNEUMATIC DURAECO FORKLIFT SERIES



### Design Features

- Enhanced traction designed for indoor and outdoor applications.

### Application

- Versatile in both indoor and outdoor applications.

### Deep Tread Design

- Deep center treads provide for enhanced traction to prevent slippage and spinning.

### M Pattern Features:

- Designed for tough indoor or outdoor applications.
- Deep center treads provide for enhanced traction to prevent slippage and spinning.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 5.00-8    | 3.00          | 17.52           | 4.72                  | 416.00              | 33.07        |
| 6.00-9    | 4.00          | 20.47           | 5.71                  | 579.00              | 56.22        |
| 6.50-10   | 5.00          | 22.05           | 6.10                  | 724.00              | 69.45        |
| 7.00-12   | 5.00          | 25.20           | 6.50                  | 904.00              | 94.80        |
| 8.15-15   | 7.00          | 26.77           | 8.27                  | 1085.00             | 119.05       |
| 250-15    | 7.00/7.50     | 27.95           | 8.86                  | 1375.00             | 151.02       |
| 8.25-15   | 6.50          | 31.50           | 7.87                  | 1520.00             | 180.78       |
| 14.00-25  | 10.00         | 52.36           | 13.78                 | 3799.00             | 899.49       |

\*For more information and a full list of available sizes, please visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID PRESS-ON BANDED TIRES | Traction with Extended Life

### SENTRY TIRE SOLID PRESS-ON BANDED FORKLIFT SERIES



#### Design

- Designed with high performance, natural rubber compounds

#### Performance

- Enhanced traction for better maneuverability

#### Endurance

- Engineered to be chunk and tear resistant to ensure excellent wear and maximum tire life

#### Energy Efficiency

- Low rolling resistance for reduced fuel and energy consumption



#### AVAILABLE SIZES

|               |                |             |                |
|---------------|----------------|-------------|----------------|
| 14x4.5x8      | Tracton/Smooth | 18x6x12.125 | Tracton/Smooth |
| 14x5x10       | Tracton/Smooth | 18x7x12.125 | Tracton/Smooth |
| 15x5x11.25    | Tracton/Smooth | 18x8x12.125 | Tracton/Smooth |
| 16x5x10.5     | Tracton/Smooth | 21x7x15     | Tracton/Smooth |
| 16x6x10.6     | Tracton/Smooth | 21x8x15     | Tracton/Smooth |
| 16.25x5x11.25 | Tracton/Smooth | 22x9x16     | Tracton/Smooth |
| 16.25x6x11.25 | Tracton/Smooth | 22x12x16    | Tracton/Smooth |
| 17x5x12.125   | Tracton/Smooth | 28x12x22    | Tracton/Smooth |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





## SOLID S PATTERN TIRES | Maximum Durability

SENTRY TIRE SOLID PNEUMATIC DURAECO FORKLIFT SERIES



### Design Features

- Designed for tough indoor or outdoor applications.

### Wheel Fitment

- Wheels available for all machine models.

### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### S Pattern Features:

- Designed for use in tough applications where maximum durability is needed.
- Ideal for tough waste/scrap recycling applications or applications where there are debris that damage a pneumatic tire's sidewall.
- Also available in Non-Marking and Click Pattern.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 9.00 x 20 | 7.00          | 8.70            | 38.60                 | 10276.00            | 286.00       |
| 8.25 x 15 | 6.50          | 8.00            | 32.40                 | 8234.00             | 213.00       |
| 8.15 x 15 | 7.00          | 8.00            | 28.20                 | 7772.00             | 139.00       |
| 7.00 x 12 | 5.00          | 6.70            | 26.30                 | 5053.00             | 106.00       |
| 600 x 9   | 4.00          | 5.90            | 21.10                 | 3200.00             | 63.00        |
| 6.50-10   | 5.00          | 6.50            | 22.60                 | 4016.00             | 64.00        |
| 500 x 8   | 3.00          | 4.70            | 17.90                 | 2414.00             | 37.00        |
| 300 x 15  | 8.00          | 10.00           | 32.80                 | 9950.00             | 268.00       |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID SD PATTERN TIRES | Perfect Balance of Tire Life and Ride Quality

SENTRY TIRE SOLID PNEUMATIC DURAECO FORKLIFT SERIES



### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

### Wheel Fitment

- Wheels available for all machine models.

### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### SD Pattern Features:

- This tread design strikes the perfect balance between tire life and operator ride quality.
- Ideal for indoor applications with deep treads for some outdoor applications.
- Designed specifically for heat release when used in “push” applications which increases tire life.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 9.00 x 20 | 7.00          | 8.70            | 38.60                 | 10276.00            | 286.00       |
| 8.25 x 15 | 6.50          | 8.00            | 32.40                 | 8234.00             | 213.00       |
| 8.15 x 15 | 7.00          | 8.00            | 28.20                 | 7772.00             | 139.00       |
| 7.00 x 12 | 5.00          | 6.70            | 26.30                 | 5053.00             | 106.00       |
| 600 x 9   | 4.00          | 5.90            | 21.10                 | 3200.00             | 63.00        |
| 6.50-10   | 5.00          | 6.50            | 22.60                 | 4016.00             | 64.00        |
| 500 x 8   | 3.00          | 4.70            | 17.90                 | 2414.00             | 37.00        |
| 300 x 15  | 8.00          | 10.00           | 32.80                 | 9950.00             | 268.00       |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID Y PATTERN TIRES | Maximum Durability and Traction

SENTRY TIRE SOLID PNEUMATIC DURAECO FORKLIFT SERIES



### Design Features

- Designed for tough indoor or outdoor applications.

### Wheel Fitment

- Wheels available for all machine models.

### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### Y Pattern Features:

- This pattern is an aggressively designed tire that is built for maximum durability and traction.
- Ideally used for operations that run on soft dirt or applications where tire traction cannot be compromised.
- Also available in Non-Marking.
- Y Pattern tires are only available through special order.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 600 x 9   | 4.00          | 5.90            | 21.10                 | 3200.00             | 63.00        |
| 7.00 x 12 | 5.00          | 6.70            | 26.30                 | 5053.00             | 106.00       |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





A yellow and black solid pneumatic loader is shown in a dark industrial setting, possibly a mine or quarry. The loader is viewed from a low angle, emphasizing its large size. A worker wearing a green hard hat and safety vest is visible through the glass of the operator's cab. The machine has a large, heavy-duty tire in the foreground. The background is dark with some industrial structures and lights visible.

# SOLID PNEUMATIC LOADER TRE SERIES

## SOLID OD PATTERN TIRES | Smooth Surface for Push Applications

### SENTRY TIRE SOLID PNEUMATIC KOLOSSUS LOADER SERIES



### OD Pattern Features:

- Uniquely designed to maximize tire wear in indoor “push” applications.
- This tire can maximize your ROI with industry leading durability.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 17.5-25   | 14.00         | 17.32           | 52.76                 | 18739.00            | 1154.12      |
| 20.5-25   | 17.00         | 20.08           | 59.06                 | 21164.00            | 1746.06      |
| 23.5-25   | 19.50         | 23.23           | 63.39                 | 23148.00            | 2383.20      |
| 26.5-25   | 22.00         | 25.59           | 67.72                 | 31967.00            | 3024.74      |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID S PATTERN TIRES | Maximum Durability

### SENTRY TIRE SOLID PNEUMATIC KOLOSSUS LOADER SERIES



#### Design Features

- Designed for tough indoor or outdoor applications.

#### Wheel Fitment

- Wheels available for all machine models.

#### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

#### S Pattern Features:

- Designed for use in tough applications where maximum durability is needed.
- Ideal for tough waste/scrap recycling applications or applications where there are debris that can damage a tire's sidewall.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 14.00-24  | 10.00         | 13.39           | 51.97                 | 8000.00             | 902.00       |
| 17.5-25   | 14.00         | 17.32           | 52.76                 | 9500.00             | 1155.00      |
| 20.5-25   | 17.00         | 20.47           | 58.27                 | 10500.00            | 1749.00      |
| 23.5-25   | 19.50         | 23.23           | 63.39                 | 13000.00            | 2387.00      |
| 26.5-25   | 22.00         | 29.13           | 67.72                 | 16000.00            | 3036.00      |
| 29.5-25   | 23.00         | 29.13           | 73.62                 | 16001.00            | 4272.40      |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





## SOLID S1D PATTERN TIRES | Perfect Balance of Tire Life and Ride Quality

SENTRY TIRE SOLID PNEUMATIC KOLOSSUS HD LOADER SERIES



### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

### Wheel Fitment

- Wheels available for all machine models.

### Tread Feature

- Provides for maximum wear in “push” type applications and traction for indoor and outdoor applications.

### S1D Pattern Features:

- Designed for use in tough applications where maximum durability is needed
- Ideal for tough waste/scrap recycling applications or applications where there's debris that can damage a tire's sidewall.
- More wearable rubber for longer tire wear
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 17.5-25   | 14.00         | 17.40           | 52.50                 | 19166.00            | 1051.59      |
| 20.5-25   | 17.00         | 20.30           | 59.00                 | 21583.00            | 1675.50      |
| 23.5-25   | 19.50         | 22.80           | 63.80                 | 22560.00            | 2358.92      |
| 26.5-25   | 22.00         | 26.40           | 66.50                 | 49914.00            | 3306.90      |
| 29.5-25   | 25.00         | 29.10           | 72.40                 | 59895.00            | 4188.74      |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID S2D PATTERN TIRES | Perfect Balance of Tire Life and Ride Quality

### SENTRY TIRE SOLID PNEUMATIC KOLOSSUS LOADER SERIES



#### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

#### Wheel Fitment

- Wheels available for all machine models.

#### Tread Feature

- Provides for maximum wear in “push” type applications and traction for indoor and outdoor applications.

### S2D Pattern Features:

- This tread design strikes the perfect balance between tire life and operator ride quality.
- Ideal for indoor applications with deep treads for some outdoor applications.
- Designed specifically for heat release when used in “push” applications which increases tire life.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 17.5-25   | 14.00         | 17.40           | 52.50                 | 19166.00            | 1057.00      |
| 20.5-25   | 17.00         | 20.30           | 57.50                 | 21583.00            | 1675.00      |
| 23.5-25   | 19.50         | 22.80           | 63.80                 | 23958.00            | 2273.00      |
| 26.5-25   | 22.00         | 26.40           | 69.00                 | 49914.00            | 3135.00      |
| 29.5-25   | 25.00         | 29.10           | 73.60                 | 59895.00            | 4092.00      |
| 35/65-33  | 28.00         | 33.50           | 80.00                 | -                   | 5214.00      |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID VD PATTERN TIRES | Traction with Maximum Durability

SENTRY TIRE SOLID PNEUMATIC DURAECO LOADER SERIES



### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

### Wheel Fitment

- Wheels available for all machine models.

### VD Pattern Features:

- Aggressive lugs allows for this tire to tackle any tough outdoor muddy applications or when superior traction is a must.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 13.00-24  | 8.50          | 14.20           | 53.10                 | 29328.00            | 674.61       |
| 14.00-24  | 8.50          | 13.78           | 52.76                 | 17600.00            | 1804.26      |
| 17.5-25   | 14.00         | 17.30           | 53.00                 | 19166.00            | 1051.59      |
| 23.5-25   | 19.50         | 22.80           | 63.80                 | 22560.00            | 2358.92      |
| 26.5-25   | 22.00         | 26.40           | 66.50                 | 49914.00            | 3306.90      |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





## SOLID ZD PATTERN TIRES | Superior Traction High Pitch Tire

SENTRY TIRE SOLID PNEUMATIC DURAECO LOADER SERIES



### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

### Wheel Fitment

- Wheels available for all machine models.

### ZD Pattern Features:

- Tire designed to resist chipping and chunking from debris.
- High pitch tires also provides for superior traction in tough and muddy applications.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 14.00-24  | 10.00         | 14.20           | 53.50                 | 29328.00            | 886.25       |
| 14.00-25  | 10.00 / 11.25 | 14.17           | 53.14                 | 29328.00            | 873.03       |
| 16.00-25  | 11.25         | 16.50           | 59.00                 | 40608.00            | 886.25       |
| 18.00-25  | 13.00         | 19.30           | 63.60                 | 47376.00            | 1960.00      |
| 20.5-25   | 17.00         | 20.50           | 59.00                 | 21583.00            | 1675.50      |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





# **SOLID PNEUMATIC SKID STEER TIRE SERIES**

## SOLID SD PATTERN TIRES | Perfect Balance of Tire Life and Ride Quality

SENTRY TIRE SOLID PNEUMATIC DURAECO SKID STEER SERIES



### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

### Wheel Fitment

- Wheels available for all machine models.

### Recommended Applications

- Asphalt or concrete surfaces
- Tight spaces where machine width is critical.

### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### SD Pattern Features:

- This tread design strikes the perfect balance between tire life and operator ride quality.
- Ideal for indoor applications with deep treads for some outdoor applications.
- Designed specifically for heat release when used in “push” applications which increases tire life.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 7.50 x 16 | 6.00          | 7.63            | 31.69                 | 5493.00             | 156.52       |
| 8.25 x 16 | 6.00          | 8.34            | 33.26                 | -                   | 207.23       |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID VD PATTERN TIRES | Traction with Maximum Durability

SENTRY TIRE SOLID PNEUMATIC DURAECO SKID STEER SERIES



### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

### Wheel Fitment

- Wheels available for all machine models.

### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### VD Pattern Features:

- Aggressive lugs allows for this tire to tackle any tough outdoor muddy applications or when superior traction is a must.
- Most sizes are also compatible with rubber tracks or steel tracks.
- Also available in Non-Marking.

| TIRE SIZE    | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|--------------|---------------|-----------------|-----------------------|---------------------|--------------|
| 8.15 x 15    | 7.00          | 8.00            | 28.20                 | 7772.00             | 139.00       |
| 6.00 x 9     | 4.00          | 5.90            | 21.10                 | 3200.00             | 63.00        |
| 570 x 12     | 3.00          | 5.50            | 22.60                 | 2866.00             | 56.21        |
| 38.5 x 14-20 | 11.00         | 13.46           | 38.18                 | 9259.00             | 374.78       |
| 36.5 x 12-20 | 8.00          | 10.80           | 36.20                 | 10600.00            | 264.00       |
| 33 x 12-20   | 8.00          | 11.91           | 33.00                 | 6614.00             | 302.00       |
| 33 x 12-16   | 8.00          | 10.82           | 33.26                 | 7055.00             | 219.36       |
| 32 x 10-20   | 7.00          | 9.20            | 31.80                 | 7220.00             | 156.53       |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





## SOLID OD PATTERN TIRES | Smooth Surface for Push Applications

SENTRY TIRE SOLID PNEUMATIC DURAECO SKID STEER SERIES



### OD Pattern Features:

- Uniquely designed to maximize tire wear in indoor “push” applications.
- This tire can maximize your ROI by providing excellent tire wear and durability.
- Also available in Non-Marking.

| TIRE SIZE  | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|------------|---------------|-----------------|-----------------------|---------------------|--------------|
| 30 x 10-20 | 7.00          | 8.90            | 30.30                 | 7220.00             | 174.00       |
| 33 x 12-20 | 8.00          | 11.02           | 32.28                 | 9024.00             | 205.03       |
| 7.50 x 16  | 6.00          | 7.00            | 31.70                 | 5493.00             | 213.00       |
| 8.25 x 16  | 6.00          | 8.34            | 33.26                 | 7260.00             | 207.23       |
| -          | -             | -               | -                     | -                   | -            |
| -          | -             | -               | -                     | -                   | -            |
| -          | -             | -               | -                     | -                   | -            |
| -          | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





# **SOLID PNEUMATIC TELEHANDLER TIRE SERIES**

## SOLID VD PATTERN TIRES | Traction with Maximum Durability

### SENTRY TIRE SOLID PNEUMATIC TELEHANDLER SERIES



#### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

#### Wheel Fitment

- Wheels available for all machine models.

#### Deep Tread Design

- Deep tread pattern allows for maximum traction and longer tread life.

### VD Pattern Features:

- Aggressive lugs allows for this tire to tackle any tough outdoor muddy applications or when superior traction is a must.
- Also available in Non-Marking.

| TIRE SIZE  | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|------------|---------------|-----------------|-----------------------|---------------------|--------------|
| 13.00-24   | 8.50          | 12.60           | 50.00                 | 14960.00            | 630.52       |
| 14.00-24   | 10.00         | 13.80           | 52.80                 | 17600.00            | 820.12       |
| 33 x 12-20 | 8.00          | 11.20           | 33.10                 | 6600.00             | 265.00       |
| 385/65-24  | 10.00         | 14.20           | 41.70                 | 13200.00            | 423.28       |
| 385/70-20  | 10.00         | 14.20           | 41.70                 | 13200.00            | 500.44       |
| 445/65-20  | 12.00         | 16.90           | 41.70                 | 14960.00            | 606.27       |
| 445/65-24  | 12.00         | 16.90           | 45.30                 | 16500.00            | 639.34       |
| -          | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)



## SOLID SD PATTERN TIRES | Perfect Balance of Tire Life and Ride Quality

SENTRY TIRE SOLID PNEUMATIC DURAECO TELEHANDLER SERIES



### Tread Feature

- Provides for maximum wear in “push” type applications and traction for indoor and outdoor

### Deflectors / Aperture Holes

- Enhances ride quality, increases heat dissipation, and maximizes the life of the tire.

### Wheel Fitment

- Wheels available for all machine models. applications.

### SD Pattern Features:

- This tread design strikes the perfect balance between tire life and operator ride quality.
- Ideal for indoor applications with deep treads for some outdoor applications.
- Designed specifically for heat release when used in “push” applications which increases tire life.
- Also available in Non-Marking.

| TIRE SIZE | RIM SIZE (IN) | TIRE WIDTH (IN) | OVERALL DIAMETER (IN) | LOAD CAPACITY (LBS) | WEIGHT (LBS) |
|-----------|---------------|-----------------|-----------------------|---------------------|--------------|
| 13.00-24  | 9.00          | 13.20           | 49.20                 | 18960.00            | 674.60       |
| 14.00-24  | 10.00         | 13.40           | 52.00                 | 22046.00            | 851.00       |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |
| -         | -             | -               | -                     | -                   | -            |

\*For more information and a full list of available sizes, please turn to page 26 for Tire Index or visit [www.sentrytire.com](http://www.sentrytire.com)





# SOLID TIRE INDEX

## FORKLIFT TIRE SERIES

### FORKLIFT K PATTERN APPLICATION LIST

| Tire Size  | Brand   | Load Capacity (lbs) | O.D. | Rim Size  | Style            |
|------------|---------|---------------------|------|-----------|------------------|
| 15x4 1/2-8 | Duraeco | 1873.9              | 15   | 3         | Solid Pneumatics |
| 16x6-8     | Duraeco | 2425                | 16.2 | 4.33      | Solid Pneumatics |
| 18x7-8     | Duraeco | 3637.6              | 18   | 4.33      | Solid Pneumatics |
| 200/50-10  | Duraeco | 3968.3              | 18.2 | 6.5       | Solid Pneumatics |
| 21x8-9     | Duraeco | 4850.2              | 20.8 | 6         | Solid Pneumatics |
| 23x10-12   | Duraeco | 6172.9              | 23.1 | 8         | Solid Pneumatics |
| 23x9-10    | Duraeco | 5952.5              | 23.1 | 6.5       | Solid Pneumatics |
| 250-15     | Duraeco | 7936.6              | 29.6 | 7.00/7.50 | Solid Pneumatics |
| 27x10-12   | Duraeco | 7716.2              | 27   | 8         | Solid Pneumatics |
| 300-15     | Duraeco | 11023.1             | 32.8 | 8         | Solid Pneumatics |
| 5.00-8     | Duraeco | 2425.1              | 18   | 3         | Solid Pneumatics |
| 6.00-9     | Duraeco | 3196.7              | 20.5 | 4         | Solid Pneumatics |
| 6.50-10    | Duraeco | 3968.3              | 23   | 5         | Solid Pneumatics |
| 7.00-12    | Duraeco | 5291                | 26   | 5         | Solid Pneumatics |
| 8.15-15    | Duraeco | 6613.8              | 28   | 7         | Solid Pneumatics |
| 8.25-15    | Duraeco | 9259.4              | 32.8 | 6.5       | Solid Pneumatics |

### FORKLIFT M PATTERN APPLICATION LIST

| Tire Size       | Brand   | Load Capacity (lbs) | O.D.  | Rim Size       | Style            |
|-----------------|---------|---------------------|-------|----------------|------------------|
| 10.00-20        | Duraeco | 13227.74            | 39.76 | 7.00/7.50/8.00 | Solid Pneumatics |
| 11.00-20        | Duraeco | 14330.05            | 40.94 | 7.00/7.50/8.00 | Solid Pneumatics |
| 12.00-20        | Duraeco | 15432.36            | 42.91 | 7.50/8.00/8.50 | Solid Pneumatics |
| 12.00-24        | Duraeco | 17196.06            | 47.24 | 8.00/8.50      | Solid Pneumatics |
| 14.00-24        | Duraeco | 23148.54            | 52.36 | 10             | Solid Pneumatics |
| 14.00-25        | Duraeco | 23148.54            | 52.36 | 10             | Solid Pneumatics |
| 140/55-9        | Duraeco | 2204.62             | 14.76 | 4              | Solid Pneumatics |
| 15x4 1/2-8      | Duraeco | 1873.93             | 14.76 | 3              | Solid Pneumatics |
| 16x6-8          | Duraeco | 2535.32             | 15.94 | 4.33           | Solid Pneumatics |
| 17 3/4x61/2-10  | Duraeco | 3306.93             | 17.72 | 5              | Solid Pneumatics |
| 180/60-10       | Duraeco | 3306.93             | 17.72 | 5              | Solid Pneumatics |
| 18x7-8          | Duraeco | 3968.32             | 17.52 | 4.33           | Solid Pneumatics |
| 200/50-10       | Duraeco | 4188.78             | 18.11 | 6.5            | Solid Pneumatics |
| 22 1/4x7 1/2-15 | Duraeco | 5291.09             | 22.24 | 5.5            | Solid Pneumatics |
| 23x10-12        | Duraeco | 6613.87             | 22.44 | 8              | Solid Pneumatics |
| 23x9-10         | Duraeco | 6613.87             | 22.24 | 6.5            | Solid Pneumatics |
| 250-15          | Duraeco | 8377.57             | 27.95 | 7.00/7.50      | Solid Pneumatics |
| 27x10-12        | Duraeco | 7716.18             | 26.18 | 8              | Solid Pneumatics |
| 28x12.5-15      | Duraeco | 10582.19            | 27.56 | 9.75           | Solid Pneumatics |
| 355/65-15       | Duraeco | 13668.66            | 31.89 | 9.75           | Solid Pneumatics |
| 4               | Duraeco | 5291.09             | 20.28 | 6              | Solid Pneumatics |
| 5.00-8          | Duraeco | 2535.32             | 17.52 | 3              | Solid Pneumatics |
| 5.50-15         | Duraeco | 4188.78             | 26.18 | 4.5            | Solid Pneumatics |
| 6.00-15         | Duraeco | 4850.17             | 26.97 | 4.5            | Solid Pneumatics |
| 6.00-9          | Duraeco | 3527.4              | 20.47 | 4              | Solid Pneumatics |
| 6.50-10         | Duraeco | 4409.25             | 22.05 | 5              | Solid Pneumatics |
| 7.00-12         | Duraeco | 5511.56             | 25.2  | 5              | Solid Pneumatics |
| 7.00-15         | Duraeco | 6613.87             | 28.35 | 5.50/6.00      | Solid Pneumatics |
| 7.50-15         | Duraeco | 7495.72             | 29.33 | 5.50/6.00      | Solid Pneumatics |
| 7.50-16         | Duraeco | 7495.72             | 30.31 | 6              | Solid Pneumatics |
| 8.15-15         | Duraeco | 6613.87             | 26.77 | 7              | Solid Pneumatics |
| 8.25-15         | Duraeco | 9259.42             | 31.5  | 6.5            | Solid Pneumatics |
| 8.25-20         | Duraeco | 11023.11            | 38.58 | 6.00/6.50      | Solid Pneumatics |
| 9.00-20         | Duraeco | 11023.11            | 38.58 | 7              | Solid Pneumatics |

### FORKLIFT PRESS-ON BANDED APPLICATION LIST

| Tire Size           | o.d. (in) | section width (in) | Weight | Available Patterns |          |                    |
|---------------------|-----------|--------------------|--------|--------------------|----------|--------------------|
|                     |           |                    |        | Smooth             | Traction | Non-Marking Smooth |
| 14 * 4 1/2-8        | 14        | 4.5                | 25     | X                  |          |                    |
| 16 x 5 x10-1/2      | 16        | 5                  | 33     | X                  | X        | X                  |
| 16 x 6 x 10-1/2     | 16        | 6                  | 40     | X                  | X        | X                  |
| 16-1/4 x 5 x 11-1/4 | 16.25     | 5                  | 33     | X                  |          | X                  |
| 16-1/4 x 6 x 11-1/4 | 16.25     | 6                  | 40     | X                  |          | X                  |
| 16-1/4 x 7 x 11-1/4 | 16.25     | 7                  | 47     | X                  |          | X                  |
| 18 x 6 x 12-1/8     | 18        | 6                  | 48     | X                  | X        | X                  |
| 18 x 7 x 12-1/8     | 18        | 7                  | 56     | X                  | X        | X                  |
| 18 x 8 x 12-1/8     | 18        | 8                  | 65     | X                  | X        | X                  |
| 21 x 7 x 15         | 21        | 7                  | 70     | X                  | X        | X                  |
| 21 x 8 x 15         | 21        | 8                  | 80     | X                  | X        | X                  |
| 22x12x16            | 22        | 12                 |        | X                  |          |                    |
| 22x8x16             | 22        | 8                  |        | X                  |          |                    |
| 22x9x16             | 22        | 9                  |        | X                  |          |                    |
| 22x12x16            | 22        | 12                 |        |                    |          | X                  |
| 28x12x22            | 28        | 12                 |        | X                  |          |                    |

### FORKLIFT: S PATTERN APPLICATIONS LIST

| Tire Size   | Brand   | Load Capacity (lbs) | O.D.  | Rim Size | Style            |
|-------------|---------|---------------------|-------|----------|------------------|
| 10.00x20    | Duraeco | 11280               | 41    | 8        | Solid Pneumatics |
| 10.00x20    | Duraeco | 11280               | 41    | 7.5      | Solid Pneumatics |
| 10.00x20    | Duraeco | 11280               | 41    | 7        | Solid Pneumatics |
| 11.00x20    | Duraeco | 11280               | 44.09 | 7        | Solid Pneumatics |
| 11.00x20    | Duraeco | 12634               | 44.09 | 8        | Solid Pneumatics |
| 12.00x20    | Duraeco | 14100               | 45.3  | 8.5      | Solid Pneumatics |
| 12.00x20    | Duraeco | 14100               | 45.3  | 8        | Solid Pneumatics |
| 12.00x24    | Duraeco | 16243               | 47.6  | 8.5      | Solid Pneumatics |
| 12.00x24    | Duraeco | 16243               | 47.6  | 8        | Solid Pneumatics |
| 15X4 1/2-8  | Duraeco | 1805                | 14.9  | 3        | Solid Pneumatics |
| 16X5-8      | Duraeco | 2030                | 16.3  | 3.5      | Solid Pneumatics |
| 16X6-8      | Duraeco | 2414                | 16.4  | 4.33     | Solid Pneumatics |
| 18X7-8      | Duraeco | 3700                | 18.1  | 4.33     | Solid Pneumatics |
| 200/50-10   | Duraeco | 4963                | 18    | 6.5      | Solid Pneumatics |
| 21X8-9      | Duraeco | 4782                | 21.1  | 6        | Solid Pneumatics |
| 23X10-12    | Duraeco | 6542                | 22.6  | 8        | Solid Pneumatics |
| 23x9-10     | Duraeco | 5831                | 23.5  | 6.5      | Solid Pneumatics |
| 250x15      | Duraeco | 8054                | 28.2  | 7        | Solid Pneumatics |
| 250x15      | Duraeco | 8054                | 28.2  | 7.5      | Solid Pneumatics |
| 27X10-12    | Duraeco | 6621                | 26    | 8        | Solid Pneumatics |
| 28X12.50-15 | Duraeco | 11731               | 28.3  | 9.75     | Solid Pneumatics |
| 300x15      | Duraeco | 9950                | 32.8  | 8        | Solid Pneumatics |
| 355/65-15   | Duraeco | 13576               | 32.8  | 9.75     | Solid Pneumatics |
| 400x8       | Duraeco | 1624                | 16.3  | 3        | Solid Pneumatics |
| 400x8       | Duraeco | 1624                | 16.3  | 3        | Solid Pneumatics |
| 5.50x15     | Duraeco | 3835                | 26.7  | 4.5      | Solid Pneumatics |
| 500x8       | Duraeco | 2414                | 17.9  | 3        | Solid Pneumatics |
| 6.00x15     | Duraeco | 3835                | 26.7  | 4.5      | Solid Pneumatics |
| 6.50-10     | Duraeco | 4016                | 22.6  | 5        | Solid Pneumatics |
| 600x9       | Duraeco | 3200                | 21.1  | 4        | Solid Click      |
| 7.00x12     | Duraeco | 5053                | 26.3  | 5        | Solid Pneumatics |
| 7.00x15     | Duraeco | 6089                | 29.4  | 5.5/6.0  | Solid Pneumatics |
| 7.50x10     | Duraeco | 4963                | 25.6  | 5.5      | Solid Pneumatics |
| 7.50x15     | Duraeco | 6723                | 31.5  | 5.5/6.0  | Solid Pneumatics |
| 7.50x16     | Duraeco | 5493                | 31.7  | 5.5/6.0  | Solid Pneumatics |
| 8.15x15     | Duraeco | 7772                | 28.2  | 7        | Solid Pneumatics |
| 8.25x12     | Duraeco | 7670                | 28.5  | 5        | Solid Pneumatics |
| 8.25x15     | Duraeco | 8234                | 32.4  | 6.5      | Solid Pneumatics |
| 8.25x20     | Duraeco | 9024                | 38.6  | 6.5      | Solid Pneumatics |
| 9.00x20     | Duraeco | 10276               | 38.6  | 7        | Solid Pneumatics |

### FORKLIFT S-CLICK PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D. | Rim Size | Style       |
|-----------|---------|---------------------|------|----------|-------------|
| 300x15    | Duraeco | 9950                | 32.8 | 8        | Solid Click |
| 7.00x12   | Duraeco | 5053                | 26.3 | 5        | Solid Click |
| 7.00x15   | Duraeco | 6089                | 29.4 | 5.5/6.0  | Solid Click |
| 8.25x15   | Duraeco | 8234                | 32.4 | 6.5      | Solid Click |

### FORKLIFT SD PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D. | Rim Size | Style            |
|-----------|---------|---------------------|------|----------|------------------|
| 10.00x20  | Duraeco | 11280               | 41   | 7.5      | Solid Pneumatics |
| 10.00x20  | Duraeco | 11280               | 41   | 7        | Solid Pneumatics |
| 11.00x20  | Duraeco | 12870               | 43.7 | 8.5      | Solid Pneumatics |
| 11.00x20  | Duraeco | 12870               | 43.7 | 7.5      | Solid Pneumatics |
| 12.00x20  | Duraeco | 13860               | 44.9 | 8.5      | Solid Pneumatics |
| 12.00x20  | Duraeco | 13860               | 44.9 | 8        | Solid Pneumatics |
| 250x15    | Duraeco | 8054                | 28.2 | 7.5      | Solid Pneumatics |
| 250x15    | Duraeco | 8054                | 28.2 | 7        | Solid Pneumatics |
| 300x15    | Duraeco | 9950                | 32.8 | 8        | Solid Pneumatics |
| 500x8     | Duraeco | 2414                | 17.9 | 3        | Solid Pneumatics |
| 6.50-10   | Duraeco | 4016                | 22.6 | 5        | Solid Pneumatics |
| 600x9     | Duraeco | 3200                | 21.1 | 4        | Solid Pneumatics |
| 7.00x12   | Duraeco | 5053                | 26.3 | 5        | Solid Pneumatics |
| 8.15x15   | Duraeco | 7772                | 28.2 | 7        | Solid Pneumatics |
| 8.25x15   | Duraeco | 8234                | 32.4 | 6.5      | Solid Pneumatics |
| 9.00x20   | Duraeco | 10276               | 38.6 | 7        | Solid Pneumatics |

### FORKLIFT Y PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D. | Rim Size | Style            |
|-----------|---------|---------------------|------|----------|------------------|
| 600x9     | Duraeco | 3200                | 21.1 | 4        | Solid Pneumatics |
| 7.00x12   | Duraeco | 5053                | 26.3 | 5        | Solid Pneumatics |

# SOLID TIRE INDEX

## LOADER TIRE SERIES

### LOADER OD PATTERN APPLICATION LIST

| Tire Size | Brand    | Load Capacity (lbs) | O.D.  | Rim Size | Style | Tire Width |
|-----------|----------|---------------------|-------|----------|-------|------------|
| 14.00-24  | Kolossus | 8000                | 52.76 | 10       |       | 13.78      |
| 16.00-25  | Kolossus | 10000               | 59.06 | 11.25    |       | 16.14      |
| 17.5-25   | Kolossus | 9500                | 52.76 | 14       |       | 17.32      |
| 18.00-25  | Kolossus | 12000               | 63.39 | 13       |       | 18.11      |
| 20.5-25   | Kolossus | 10500               | 59.06 | 17       |       | 20.08      |
| 23.5-25   | Kolossus | 13000               | 63.39 | 19.5     |       | 23.23      |
| 26.5-25   | Kolossus | 16000               | 67.72 | 22       |       | 25.59      |

### LOADER S PATTERN APPLICATION LIST

| Tire Size | Brand    | Load Capacity (lbs) | O.D.  | Rim Size | Style | Tire Width |
|-----------|----------|---------------------|-------|----------|-------|------------|
| 14.00-24  | Kolossus | 8000                | 51.97 | 10       |       | 13.39      |
| 17.5-25   | Kolossus | 9500                | 52.76 | 14       |       | 17.32      |
| 20.5-25   | Kolossus | 10500               | 58.27 | 17       |       | 20.47      |
| 23.5-25   | Kolossus | 13000               | 63.39 | 19.5     |       | 23.23      |
| 26.5-25   | Kolossus | 16000               | 67.72 | 22       |       | 29.13      |
| 29.5-25   | Kolossus | 16001               | 73.62 | 23       |       | 29.13      |

### LOADER SD PATTERN APPLICATION LIST

| Tire Size | Brand    | Load Capacity (lbs) | O.D.  | Rim Size | Style           | Tire Width |
|-----------|----------|---------------------|-------|----------|-----------------|------------|
| 16.00-25  | Duraeco  | 40608               | 59    | 11.25    | Solid Pneumatic | 16.5       |
| 17.5-25   | Kolossus | 19166               | 53    | 14       | Solid Pneumatic | 17.3       |
| 20.5-25   | Duraeco  | 21583               | 59    | 17       | Solid Pneumatic | 20.5       |
| 20.5-25   | Kolossus | 21583               | 59    | 17       | Solid Pneumatic | 20.5       |
| 23.5-25   | Duraeco  | 22560               | 63.8  | 19.5     | Solid Pneumatic | 22.8       |
| 26.5-25   | Kolossus | 49914               | 66.5  | 22       | Solid Pneumatic | 26.4       |
| 29.5-25   | Duraeco  | 59895               | 72.4  | 25       | Solid Pneumatic | 29.7       |
| 29.5-25   | Kolossus | 59895               | 72.4  | 25       | Solid Pneumatic | 29.7       |
| 35x65/33  | Duraeco  |                     | 79.92 | 28       | Solid Pneumatic | 33.46      |
| 50x16-24  | Duraeco  |                     | 49.21 | 11.25    | Solid Pneumatic | 15.74      |

### LOADER VD PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D.  | Rim Size | Style           | Tire Width |
|-----------|---------|---------------------|-------|----------|-----------------|------------|
| 13.00-24  | Duraeco | 29328               | 53.1  | 9        | Solid Pneumatic | 14.2       |
| 14.00-24  | Duraeco | 17600               | 52.76 | 10       | Solid Pneumatic | 13.78      |
| 17.5-25   | Duraeco | 19166               | 53    | 14       | Solid Pneumatic | 17.3       |
| 23.5-25   | Duraeco | 22560               | 63.8  | 19.5     | Solid Pneumatic | 22.8       |
| 26.5-25   | Duraeco | 49914               | 66.5  | 22       | Solid Pneumatic | 26.4       |

### LOADER ZD PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D.  | Rim Size | Style           | Tire Width |
|-----------|---------|---------------------|-------|----------|-----------------|------------|
| 14.00-24  | Duraeco | 29328               | 53.5  | 10       | Solid Pneumatic | 14.2       |
| 14.00-25  | Duraeco | 29328               | 53.14 | 10       | Solid Pneumatic | 14.17      |
| 16.00-25  | Duraeco | 40608               | 59    | 11.25    | Solid Pneumatic | 16.5       |
| 18.00-25  | Duraeco | 47376               | 63.6  | 13       | Solid Pneumatic | 19.3       |
| 20.5-25   | Duraeco | 21583               | 59    | 17       | Solid Pneumatic | 20.5       |

## SKID STEER TIRE SERIES

### SKID STEER VD PATTERN APPLICATION LIST

| Tire Size  | OEM Tire Size | Brand   | Load Capacity | O.D.  | Rim Size |
|------------|---------------|---------|---------------|-------|----------|
| 23x8.50-12 | 570-12        | Duraeco | 3740          | 22.8  | 5        |
| 30x10-16   | 10x16.5       | Duraeco | 4963          | 30.2  | 6        |
| 30x8.5-16  | 10x16.5       | Duraeco | 4840          | 30.1  | 8.2      |
| 32x10-20   | 10x16.5       | Duraeco | 7220          | 31.8  | 7        |
| 33x12-16   | 12x16.5       | Duraeco | 4840          | 33.26 | 8        |
| 33x12-20   | 12x16.5       | Duraeco | 6600          | 32.68 | 8        |
| 36.5x12-20 | 14x17.5       | Duraeco | 10600         | 36.2  | 8        |
| 38.5X14-20 | 14x17.5       | Duraeco | 9240          | 38.18 | 11       |
| 570x12     | 5.70-12       | Duraeco | 2860          | 22.6  | 3        |
| 600x9      |               | Duraeco | 3200          | 21.1  | 4        |
| 8.15x15    | 8.15-15       | Duraeco | 7772          | 28.2  | 7        |

### SKID STEER SD PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D.  | Rim Size | Style           |
|-----------|---------|---------------------|-------|----------|-----------------|
| 750 x 16  | Duraeco | 5493                | 31.69 | 6        | Solid Pneumatic |
| 825 x 16  | Duraeco |                     | 33.26 | 6        | Solid Pneumatic |

### SKID STEER OD PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D.  | Rim Size | Style           |
|-----------|---------|---------------------|-------|----------|-----------------|
| 30x10-20  | Duraeco | 7220                | 30.3  | 7        | Solid Pneumatic |
| 33x12-20  | Duraeco | 9024                | 32.28 | 8        | Solid Pneumatic |
| 7.50x16   | Duraeco | 5493                | 31.7  | 6        | Solid Pneumatic |
| 825 x 16  | Duraeco | 7260                | 33.26 | 6        | Solid Pneumatic |

## TELEHANDLER TIRE SERIES

### TELEHANDLER VD PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D. | Rim Size | Style           | Tire Width |
|-----------|---------|---------------------|------|----------|-----------------|------------|
| 13.00-24  |         | 14960               | 50   | 8.5      | Solid Pneumatic | 12.6       |
| 14.00-24  | Duraeco | 17600               | 52.8 | 10       | Solid Pneumatic | 13.8       |
| 33x12-20  | Duraeco | 6600                | 33.1 | 8        | Solid Pneumatic | 11.2       |
| 385/65-24 |         | 13200               | 41.7 | 10       | Solid Pneumatic | 14.2       |
| 385/70-20 |         | 13200               | 41.7 | 10       | Solid Pneumatic | 14.2       |
| 445/65-20 |         | 14960               | 41.7 | 12       | Solid Pneumatic | 16.9       |
| 445/65-24 |         | 16500               | 45.3 | 12       | Solid Pneumatic | 16.9       |

### SKID STEER SD PATTERN APPLICATION LIST

| Tire Size | Brand   | Load Capacity (lbs) | O.D.  | Rim Size | Style           |
|-----------|---------|---------------------|-------|----------|-----------------|
| 750 x 16  | Duraeco | 5493                | 31.69 | 6        | Solid Pneumatic |
| 825 x 16  | Duraeco |                     | 33.26 | 6        | Solid Pneumatic |



## Sentry Tire

1440 E. Cedar St. Ontario, CA 91761

PH: (888) 858-8892 | FAX: (909) 230-5553

Info@sentrytire.com

